




TLS-MT20

48V magnetic track system




TLS-MT20 Series


TLS-MT20 is a DC48V magnetic track system of 20mm width. Its magnetic design offers great DIY convenience to flexibly combine linear modules, spotlights, pendant lights and decorative neon flex in one system, achieving all your lighting demands like basic flood lighting, accent lighting or decorative lighting, suitable for residential villas, hotel clubs, entertainment venues or commercial exhibitions, etc.

System overview


Straight track



Curve track




Spotlight Module




Decorative Module



Linear Module



Optics



Corner




CCT




Curved track

Combine with straight track for more possibilities



Corner accessory

Five finished accessories, no cutting required
Seamless splicing, excellent aesthetics



Easy installation



DIY combination of modules

Easy installation, pre-embed track and attach modules in seconds magnetically.

Modular system, satisfies various lighting demands.

Movable and angle adjustable, add flexibility to light designs.

Low-voltage, safe to touch and use.





3CCT Dial-switch


3000 K 3800 K 5000 K

All-metal housing
Minimalist appearance




Adaptive Voltage24-48V

24V Magnetic Track



48V Magnetic Track



Track accessories

Electrical connection accessory



Power feeder of track
Model: TLS-M261
Size: L147×W19×H17.3mm
Applicable model: All straight track



I-shaped electrical connector (recessed type)
Model: TLS-M265
Size: L70×W11.5×H2.1mm(Splicing bar)
L78×W19×H17mm(Power feeder)
Applicable model: TLS-MR2XOA
TLS-MR2XOB
TLS-MR2XOC



I-shaped electrical connector (Surface)
Model: TLS-M266
Size: L55×W22×H4.3mm(Splicing bar)
L78×W19×H17mm(Power feeder)
Applicable model: TLS-MS2X0



Electrical connector
Model: TLS-M264
Size: L147×W19×H17.3mm
Applicable model:
All straight track corner

Power supply



Magnetic power
Model: MT20-HDRV100H48S-M
Size: L248×W22.5×H46mm
Input voltage: 220-240VAC
Output: DC48V
Power: 100W
Applicable model: All straight track



Magnetic power
Model: MT20-HDRV200H48S-M
Size: L305×W22.5×H46mm
Input voltage: 220-240VAC
Output: DC48V
Power: 200W
Applicable model: All straight track



Power supply
Model: BN-V48-100P
Size: L350×W30×H18mm
Input voltage: 220-240VAC
Output: DC48V
Power: 100W
Applicable model: All straight track



Power supply
Model: BN-V48-250P
Size: L400×W40×H22mm
Input voltage: 220-240VAC
Output: DC48V
Power: 250W
Applicable model: All track

End cap



Model: EC-MH20
Material: Aluminum
Size: L52×W27.2×H5.5mm
Applicable model: TLS-MH2X0



Model: EC-MR20
Material: Aluminum
Size: L46.5×W27.5×H5.5mm
Applicable model: TLS-MR2X0(A)
TLS-MR2X0(B)
TLS-MR2X0(C)



Model: EC-MS20
Material: Aluminum
Size: L27.6×W27.5×H2.5mm
Applicable model: TLS-MS2X0

Corner accessory



L-shaped (Downward)
Model: L90-MR20(A)
Material: AL6063-T5
Size: L95×W95×H46.5mm
Applicable model: TLS-MR2X0(A)



L-shaped (Inward)
Model: L90N-MR20(A)
Material: AL6063-T5
Size: L80×W80×H64mm
Applicable model: TLS-MR2X0(A)



L-shaped (Downward)
Model: L90-MR20(B)
Material: AL6063-T5
Size: L95×W95×H46.5mm
Applicable model: TLS-MR2X0(B)



L-shaped (Inward)
Model: L90N-MR20(B)
Material: AL6063-T5
Size: L80×W80×H64mm
Applicable model: TLS-MR2X0(B)

Installation accessory



Track bind cover
Model: CV-M20FB
Material: PVC
Size: L1000×W25.7×H5.6mm
Applicable model: All straight track




Ceiling accessory
Model: TLS-M271
Material: SPC
Size: L67.5×W31.5×H7.5mm
Applicable model: TLS-MS2X0
TLS-MH2X0



Pendant accessory
Model: TLS-M272
Material: AL6063-T5
Size: L30×W22×H4.3mm
Applicable model: TLS-MS2X0
TLS-MH2X0



Ceiling screw
Model: CL-01
Material: Fe
Size: M3.5×40mm
Applicable model: TLS-MR2X0(A)
TLS-MR2X0(B)
TLS-MR2X0(C)



L-shaped (Downward)
Model: L90-MR20(C)
Material: AL6063-T5
Size: L95×W95×H46.5mm
Applicable model: TLS-MR2X0(C)



L-shaped (Inward)
Model: L90N-MR20(C)
Material: AL6063-T5
Size: L80×W80×H64mm
Applicable model: TLS-MR2X0(C)



L-shaped (Downward)
Model: L90-MS20
Material: AL6063-T5
Size: L50×W50×H27.3mm
Applicable model: TLS-MS2X0



L-shaped (Inward)
Model: L90N-MS20
Material: AL6063-T5
Size: L50×W50×H27.3mm
Applicable model: TLS-MS2X0



L-shaped (Downward)
Model: L90-MH20
Material: AL6063-T5
Size: L50×W50×H52mm
Applicable model: TLS-MH2X0



L-shaped (Inward)
Model: L90N-MH20
Material: AL6063-T5
Size: L80×W80×H27.2mm
Applicable model: TLS-MH2X0



L-shaped Adjustable (Downward)
Model: L90-MH20(A)
Material: AL6063-T5
Size: L120×W27.2×H52mm
Applicable model: TLS-MH2X0



X-shaped Adjustable (Downward)
Model: X90-MH20(A)
Material: AL6063-T5
Size: L120×W120×H52mm
Applicable model: TLS-MH2X0



CASambi Control
Model: 1200EN1812-CAS-W0-BLDV48
Size: L42.6×W18×H8.1mm
Input voltage: 48VDC
Output signal:DALI
Output DALI Max.current:180mA
Control devices:≤64
Control groups:≤8
Certification:CE,UKCA
Others:Controller should be used with DALI dimming modules.




T-shaped Adjustable (Downward)
Model: T90-MH20(A)
Material: AL6063-T5
Size: L120×W60×H52mm
Applicable model: TLS-MH2X0

Systematic lighting, Effortless assembly

ECO Straight Track

Ceiling / Pendant track




TLS-ECO-MS2X0 (x:1/2/3 M)

Installation: Ceiling / Pendant
Material: AL6063-T5
Coating: Black
Size: 26.4×27.5×1000/2000/3000mm

Rated current: 7.5A

Operating Voltage	Maximum power
24V	180W
48V	360W




TLS-ECO-MH2X0 (x:1/2/3 M)

Installation: Ceiling / Pendant
Material: AL6063-T5
Coating: Black
Size: 26.4×54×1000/2000/3000mm

Rated current: 7.5A

Operating Voltage	Maximum power
24V	180W
48V	360W

Trimless recessed track




TLS-ECO-MR2X0 (x:1/2/3 M)
3mm gypsum board

Installation: Trimless recessed
Material: AL6063-T5
Coating: Black
Size: 50×54×1000/2000/3000mm
Opening Size: 30×1000/2000/3000mm

Rated current: 7.5A

Operating Voltage	Maximum power
24V	180W
48V	360W



TLS-ECO-MR2X0(A) (x:1/2/3 M)
12.5mm gypsum board

Installation: Trimless recessed
Material: AL6063-T5
Coating: Black
Size: 70×52.7×1000/2000/3000mm
Opening Size: 30×1000/2000/3000mm

Rated current: 7.5A

Operating Voltage	Maximum power
24V	180W
48V	360W

Track accessories

Electrical connection accessory



L-shaped (Downward)

Model: L90-ECO-MH20
Material: PC
Size: L99.5×W99.5×H46mm
Applicable model: TLS-ECO-MH2X0
TLS-ECO-MR2X0
TLS-ECO-MR2X0(A)



L-shaped (Downward)

Model: L90-ECO-MS20
Material: PC
Size: L99.5×W99.5×H21mm
Applicable model: TLS-ECO-MS2X0



L-shaped (Downward)

Model: L90-ECO-M281
Material: PC
Size: L143×W16.2×H17mm
Applicable model: TLS-ECO-MH2X0
TLS-ECO-MR2X0
TLS-ECO-MR2X0(A)
TLS-ECO-MS2X0

ECO End cap



Model: EC-ECO-MH20

Material: PC
Size: L52×W26×H6.3mm
Applicable model: TLS-ECO-MH2X0
TLS-ECO-MR2X0
TLS-ECO-MR2X0(A)



Model: EC-ECO-MS20

Material: PC
Size: L26.5×W21.2×H6.8mm
Applicable model: TLS-ECO-MS2X0

Installation accessory



Pendant accessory

Model: TLS-ECO-M280
Material: AL6063-T5
Size: L33×W22.6×H2000mm
Applicable model: TLS-ECO-MS2X0
TLS-ECO-MH2X0

Spotlights module

**MT20S-30**

Φ30mm spotlight

**MT20S-42**

Φ42mm spotlight


**MT20S-52**

Φ52mm spotlight

**MT20SZ-65**

Φ65mm zoom spotlight

Optics



Linear module

 | Easy installation


MT20GW

Wall washer




MT20FD

Diffuser




MT20LA

Asymmetric




MT20FP

Prismatic









MT20LS

Double Asymmetric




Mask




Wall washer**Grating****Diffuser**


Prismatic



Asymmetric



Double Asymmetric



Block Frosted



 | Easy installation

MT20NK-25

Round neon






MT20CD



Round tube



MT20CD(A)

Cross-track round tube





Case



