

FTM-25PRO/35PRO



Item:	FTM-25PRO	FTM-35PRO	Performance		
Light Brightness	100lumens	100lumens	Lighting Time in Rainy day	>10 days	>10 days
Solar panel			Control Mode	Button Switch, ON/OFF Long Press 1.5s	Button Switch, ON/OFF Long Press 1.5s
Power	Monocrystalline, 5V/ 1.9W	Monocrystalline, 5V/ 1.9W	Lighting Mode (Remote Control)	M1: 100LM (5H) + 25LM Till dawn M2: 50LM Till dawn	M1: 100LM (5H) + 25LM Till dawn M2: 50LM Till dawn
Li-ion battery			Mode Indication	M1: Red, M2: Green	M1: Red, M2: Green
Capacity	3.7V 7.4WH 2.0AH/PC	3.7V 7.4WH 2.0AH/PC	Capacity Indication	Green: ≥70%; Orange: 30%-70%; Red: <30%	Green: ≥70%; Orange: 30%-70%; Red: <30%
Charging / Discharging Temp	0~45℃ / ~-20~60℃	0~45℃ / ~-20~60℃	Core technology	ALS 2.3	ALS 2.3
Charging Time	5.2H	5.2H	IP	IP54	IP54
LED (OSRAM)	2835, 24pcs	2835, 24pcs	Material	Aluminium & PC	Aluminium & PC
Color Temp	3000K, Ra>70	3000K, Ra>70			
Efficiency	160lm/W	160lm/W			
Types of Lighting	Transparent	Transparent			

